

IP Television Headend

> DVB-S2 LAN-Caster for DSB over IP (774)

The MediaStar Evolution 774 LAN-Caster allows digital satellite TV and Radio channels, (DVB-S or DVB-S2), to be streamed onto an IP network. Connect a DVB-S/S2 LNB feed to the LAN-Caster and use the simple browser based control interface to stream up to 11 channels from a single RF multiplex to any networked PC using the MediaStar Evolution desktop viewing software (Part 761) or video screen with MediaStar Evolution Digital Media Decoders (Parts 760 and 780).

The unit is a 'hot swappable' blade that is used in conjunction with the MediaStar Evolution Chassis (Part 770). The Blade has IP Browser/RS232/USBv1.1 control interfaces and is built around an ultra reliable dual-core engine running under Linux.

Included within the scope of delivery:
774 DVB-S2 Blade; Quick Start Guide; IP address label;
RJ45 Cat-5 blue patch cable.



Specifications

Signal Input

- RF input of Digital Satellite Television (DVB-S2) TV and radio channels via a 75ohm type F female connector
- Delivers up to 11 channels from an unscrambled DVB-S2 Multiplex
- Supports both SD and HDTV
- RF loopthrough for connection to additional MediaStar DVB-S2 LAN-Caster units

Video Output Streaming Protocols

- Unicast/Multicast; UDP/RTP/RTSP 10/100 Base-T network interface for streaming to the network
- SAP

Management and Control

- IP:10/100 Base-T interface to the on-board HTML browser interface
- Serial port: RS232 interface for control and Configuration
- USB: USBv1.1 interface for control and configuration

Configuration and Monitoring

- On-board HTML setup browser. Choose up to 11 individual channels from an unscrambled DVB-S2 MUX. Select channels to stream across the network and remove at any time. Scan through available DVB-S2 multiplexes for listing in a MUX Selection Table

- Multicast and Unicast address for output of video stream
- Control additional LAN-Caster units from a single web interface via multicast link
- Password protected; Enablement Code for addition of features
- Static IP address or DHCP assignment of DVB-S2 LAN-Caster unit
- Supports Netmask, Gateway Address, DNS Server Addressing
- Telnet: 3rd party connectivity via TCP control such as Touch Panel interfaces
- SNMP: monitoring of key operating functions reported via on-board SNMP agent

Power: 3 Watts (from 770 Rack)
Weight: 300g (card only)
Dimensions: Single 770 Rack slot (1 of 9)
Environmental: 0 - 40°C; 32 - 104°F
Approvals: FCC, CE, CB

Companion Models & Accessories:

760 & 780 Digital Media Decoders
761 Desktop Viewing Application
762 Evolution Administrator Software
770 Rack and Mount Kit
777 DVB-S2 Stand Alone Unit Unit