

C2-1350 Specifications

Video Inputs

Television Standards	NTSC, PAL, PAL-M, PAL-N, SECAM
Composite Video	1x via BNC
YC (S-Video)	1x via 4-Pin Mini-DIN Connector
YUV /YPbPr	1x via 3-BNC

Computer Input

RGB/YPbPr	1x via HD15
Format - Analog	RGBHV, RGBS, RGsB, YPbPr
Sync	TTL Level, 10KΩ, Pos or Neg
Termination	Auto-terminating into 75Ω
R-G-B Level Range	0.5-2.0 Vp-p
Scan Rate Detection	Automatic
PC Resolutions	Any up to 2048x2048
HDTV Resolutions	Any up to 1080p/60
Max Horiz Scan Rate	150KHz
Computer Compatibility	PC, Macintosh, Workstations

Video Outputs

Television Standards	NTSC, PAL, PAL-M, PAL-N, SECAM
Impedance	75Ω
Composite Video	1x via BNC
YC (S-Video)	1x via 4-PIN Mini-DIN
YUV, YPbPr	1x via 3-BNC (shared w RGB Out)

Computer Outputs (2x)

Format - Analog	RGBHV, RGBS, RGsB, YPbPr
Connectors	1x HD-15 Female and 1x 5-BNC
R-G-B Level	0.7 Vp-p
PC Resolutions	Any up to 2048x2048
HDTV Resolutions	Any up to 1080p
Vertical Refresh Rate	Any to 250Hz

General

Size and Position	Automatic via AutoSet or Manual
Image Size	User-Definable Presets
Image Freeze	One Video Frame
Settings Memory	Non-Volatile
Zoom Range	Variable to 10X Zoom
Shrink Range	Variable to 10%
Image Mirroring	Horizontal and/or Vertical
Horizontal Filtering	Full Digital
Conversion Technology	Proprietary – CORIO®2
Color Resolution	24-bit (16.8 Million Colors)
Frame Rate Conversion	Temporal
Sampling Rate	108MHz
Digital Sampling	24-bit, 4:4:4 format
Firmware Memory	Flash, Upgradeable via RS-232
Video Encoder	8-bit Digital
Video Decoder	9-bit Digital

De-Interlacing (NTSC-PAL)	Pixel-level Motion Adaptive
Comb Filter Decoding	Adaptive
Film Mode (NTSC)	3:2 Pulldown
Video Adjustments	Contrast, Brightness, Saturation, Hue (NTSC), R-G-B Levels

Audio Input/Output

Inputs	4x Unbalanced via Terminals
Output	Unbalanced via Terminals

Operational Modes

Key	Chromakey or Lumakey
Mix	PC to/from Video
PIP	Variable Window Size & Position

Genlock Adjustments

Subcarrier Lock Range	+/- 200Hz for NTSC Operation (+/- 250Hz for PAL Operation)
Subcarrier Phase	+/- 180° Adjustment

Control Methods

Local	via Front Panel Buttons & OSD
RS-232 Interface	via D9 Female Connector
Infrared Remote	via IRC-5 Remote Unit
Input Expansion Control	via D-15 Options Connector

Warranty

Limited Warranty	2 Years Parts and Labor
------------------	-------------------------

Regulatory Compliance

Main Units	FCC, CE, RoHS
Power Supplies	UL, CUL, CE, PSE, GS, RoHS

Mechanical

Size (H-W-D)	41.5x218x150mm(1.63"x8.6"x5.9")
Weight (Net)	1.26kg (2.77 lbs)

Environmental

Operating Temperature	0° to +50° C (+32° to +122° F)
Operating Humidity	10% to 85%, Non-condensing
Storage Temperature	-10° to +70° C (+14° to +158° F)
Storage Humidity	10% to 85%, Non-condensing

Power Requirement

External Power Supply	12VDC@1A
-----------------------	----------

Accessories Included

1x Operations Manual	C2-1000 Series
1x Power Adapter	US, UK or Euro

Product Item Numbers

C2-1350	Universal Video Switcher/Scaler
---------	---------------------------------

Optional Accessories

IRC-5	Infrared Remote Control
RM-220	Single/Dual Rackmount Kit
S2 Series	Input Expansion Switchers
1x Control Software	Downloadable from website

