

1T-MX-3141 Series Specifications

Video Inputs

1T-MX-3141PCA 4x RGB/YPbPr via HD-15
 1T-MX-3141CSVA 4x CV via RCA + 4x S-Video
 1T-MX-3141HDA 4x YPbPr via RCA

Stereo Audio Inputs

1T-MX-3141PCA 4x via 3.5mm Mini -Stereo
 1T-MX-3141CSVA 4x via RCA (R/L)
 1T-MX-3141HDA 4x via RCA + 4x Coaxial via RCA

Video Outputs

1T-MX-3141PCA 1x RGB/YPbPr via HD-15
 1T-MX-3141CSVA 1x CV via RCA + 1x S-Video
 1T-MX-3141HDA 1x YPbPr via RCA

Stereo Audio Outputs

1T-MX-3141PCA 1x via 3.5mm Mini -Stereo
 1T-MX-3141CSVA 1x via RCA (R/L)
 1T-MX-3141HDA 1x via RCA + 1x Coaxial via RCA

Performance

Video Bandwidth 300MHz +
 Video Impedance 75Ω
 Video Level Unity, Nominal 1V p-p
 Audio Bandwidth 20Hz to 20 KHz
 Audio Impedance 20KΩ Analog, 75Ω Coaxial
 Audio Level Unity, Nominal (S/PDIF .5-1Vp-p)
 Television Standards NTSC, PAL, HDTV

Supported Signals

1T-MX-3141PCA PC: VGA, SVGA, XGA, SXGA
 UXGA (1600x1200),
 WUXGA (1920x1200)
 HDTV: 480i, 576i, 480p, 576p, 720p, 1080i, 1080p
 1T-MX-3141CSVA Composite, S-Video: NTSC&PAL
 HDTV: 480i, 576i, 480p, 576p, 720p, 1080i, 1080p

Mechanical

Size (H-W-D) 48x292x176mm (1.87"x11.5"x7")
 Weight (Net) 1.47 kg (3.25 lbs)

Warranty

Limited Warranty 2 Years Parts and Labor

Environmental

Operating Temperature 0° to +50° C (+32° to +122° F)
 Operating Humidity 10% to 90%, Non-condensing
 Storage Temperature -10° to +60° C (+14° to +140° F)
 Storage Humidity 10% to 90%, Non-condensing

Power Requirement

External Power Supply 5VDC@2A - Locking DC

Regulatory Approvals

Switcher Units FCC, CE, RoHS
 Power Supplies UL, CUL, CE, PSE, GS, RoHS

Accessories Included

1x Power Adapter US, UK or Euro
 1x IR Remote Control
 1x Rackmount Kit
 1x Operations Manual

Product Item Numbers

1T-MX-3141PCA 4x1 PC/HD with Stereo
 1T-MX-3141CSVA 4x1 CV or S-Video with Stereo
 1T-MX-3141HDA 4x1 HDTV with Stereo

