

S2-110CV, S2-105CV/CVA Specifications

Video Inputs/Outputs

S2-105CV Inputs	5x via BNC w/Loop thru
S2-105CVA Inputs	5x via BNC w/Loop thru
S2-110CV inputs	10x via BNC
All Product Outputs	2x via BNC

Video Characteristics

Bandwidth	>80 MHz
Accommodated Formats	NTSC, PAL Composite Video

Audio Inputs/Outputs (S2-105CVA Only)

Inputs	5x via Terminal Connectors
Output	1x via Terminal Connectors

Audio Characteristics (S2-105CVA Only)

Analog	Balanced or Unbalanced
Frequency Response	100KHz +/- 3dB

Control

Standalone Operation	Push Button, IR, RS-232
From C2 Series Device	via D-15 OPTION Cable

Mechanical

Size (H-W-D)	41.5x218x150mm(1.63"x8.6"x5.9")
S2-105CV Weight (Net)	1.26kg (2.77 lbs)
S2-105CVA Weight(Net)	1.30kg (2.86 lbs)
S2-110CV Weight (Net)	1.26kg (2.77 lbs)

Warranty

Limited Warranty	2 Years Parts and Labor
------------------	-------------------------

Environmental

Operating Temperature	0° to +50° C (+32° to +122° F)
Operating Humidity	10% to 85%, Non-condensing
Storage Temperature	-10° to +70° C (+14° to +158° F)
Storage Humidity	10% to 85%, Non-condensing

Power Requirement

All Models	12VDC@1A (Note 1)
------------	-------------------

Regulatory Approvals

Expansion Units	FCC, CE, RoHS
Power Supplies	UL, CUL, CE, PSE, GS, RoHS

Product Item Numbers

S2-105CV Switcher	5x2 Composite Video
S2-105CVA Switcher	5x2 Composite Video w/Stereo
S2-110CV Switcher	10x2 Composite Video

Accessories Included

1x Operations Manual	S2 Series
1x Power Adapter	US, UK or Euro
1x OPTION Interconnect	D-15M to D-15M & D-15F Cable

Optional Accessories

RM-220	Single/Dual Rackmount Kit
IRC-5	Infrared Remote Control

Note

(1) The C2-1000 & C2-2000 series products supply enough power via the OPTION Connector for one 5-Input S2 unit. Additional S2 units may be powered with separate power adapters (included).

