



## S2-110YC, S2-105YC/YCA Specifications

### Video Inputs/Outputs

S2-105YC Inputs	5x via 4-Pin Mini-DIN w/Loop thru
S2-105YCA Inputs	5x via 4-Pin Mini-DIN w/Loop thru
S2-110YC Inputs	10x via 4-Pin Mini-DIN
All Product Outputs	2x via 4-Pin Mini-DIN

### Video Characteristics

Bandwidth	>80 MHz
Accommodated Formats	NTSC, PAL Composite Video

### Audio Inputs/Outputs (S2-105YCA Only)

Inputs	5x via Terminal Connectors
Output	1x via Terminal Connectors

### Audio Characteristics (S2-105YCA Only)

Analog	Balanced or Unbalanced
Frequency Response	100KHz +/- 3dB

### Control

Standalone Operation	Push Button, IR, RS-232
From C2 Series Device	via D-15 OPTION Connector

### Mechanical

Size (H-W-D)	41.5x218x150mm(1.63"x8.6"x5.9")
S2-105YC Weight (Net)	1.10kg (2.42 lbs)
S2-105YCA Weight (Net)	1.14kg (2.51 lbs)
S2-110YC Weight (Net)	1.10kg (2.42 lbs)

### Warranty

Limited Warranty	2 Years Parts and Labor
------------------	-------------------------

### Environmental

Operating Temperature	0° to +50° C (+32° to +122° F)
Operating Humidity	10% to 85%, Non-condensing
Storage Temperature	-10° to +70° C (+14° to +158° F)
Storage Humidity	10% to 85%, Non-condensing

### Power Requirement

All Models	12VDC@1A (Note 1)
------------	-------------------

### Regulatory Approvals

Expansion Units	FCC, CE, RoHS
Power Supplies	UL, CUL, CE, PSE, GS, RoHS

### Product Item Numbers

S2-105YC Switcher	5x2 YC Video
S2-105YCA Switcher	5x2 YC Video w/Stereo Audio
S2-110YC Switcher	10x2 YC Video

### Accessories Included

1x Operations Manual	S2 Series
1x Power Adapter	US, UK or Euro
1x OPTION Interconnect	D-15M to D-15M & D-15F Cable

### Optional Accessories

RM-220	Single/Dual Rackmount Kit
IRC-5	Infrared Remote Control

### Note

(1) The C2-1000 & C2-2000 series products supply enough power via the Options Connector for one 5-Input S2 unit. Additional S2 units may be powered with separate power adapters which are included.

